



Feature

- Side plate changeable for ODM option
- TV Out and S-Video support
- 4 X USB ports
- One LAN ports (Two LAN option)
- Internal USB for Smart Card Reader and WLAN (option)

Specification	Model	Biostar RT275		
Processor	CPU / Chip Set	VIA C7 1GHz NanoBGA2 Process / CN700 Chipset · North bridge VIA VT8237R Plus		
BIOS	BootROM	4Mb BootROM		
Memory	RAM	One SO-DIMM socket supports DDR2 1GB		
Display	Resolution	up to 1920x1440 32bit color		
	Video Memory	16M to 64M shared with system DDR RAM		
	Display Data Control	Integrated VIA Uni-ChromePro AGP graphics		
Audio		VIA VT1618 AC'97 codec		
Storage		1x ATA133 IDE slots IDE ; 2xSATA And Support 1GB DOM		
I/O Interface	PS2 Port	x 2		
	USB Port (2.0)	x 4		
	Serial Port	x 1		
	Video	VGA	x 1(D-sub 15pin)	
		S-Video	x 1	
	Audio	Mic-in	x 1	
		Line-in	x 1	
Line-out		x 1(Speaker out jack)		
Networking	LAN	x 1 (RJ-45, 10/100Base T)		
Power	Power Supply	48W, DC 12V/4A External power adapter		
Mounting	Feet Stand	H or V	H / V	
Security	Kensington Lock	Yes		
OS Supports		Embedded Windows XP SP2 中文版		
BIOS Support		Wake On LAN (Support PXE)		
Dimension		22.75cm(L)x16.38cm(W) ;Box: 25cm(H)x4.5cm(W)x23cm(D)		
Regulatory Compliance		BSM/CE/ FCC		



Yuan Gane Co.,Ltd.

1F, No.17, Aly 2, Lane 402, Yanshou St,
Taipei, Taiwan, R.O.C.

Tel: 886-2-2763-7069

Fax: 886-2-2748-6718

<http://www.thin-plus.com.tw>